



1200 /3	-	-	-	x	x	x	x	x	x	x	9<20
1200 /4	-	-	-	x	x	x	x	x	x	x	9<20
1200 /5	-	-	-	x	x	x	x	x	x	x	9<20
1400 /4	-	-	-	x	x	x	x	x	x	x	9<20
1600 /4	-	-	-	x	x	x	x	x	x	x	9<20
1600 /5	-	-	-	x	x	x	x	x	x	x	9<20
1800 /4	-	-	-	x	x	x	x	x	x	x	9<20
1800 /5	-	-	-	x	x	x	x	x	x	x	9<20

\*na życzenie klienta wykonujemy indywidualne szerokości taśm transportowych

## Minimalne średnice bębnow

Typ taśmy/ilość przekładek	Rdzeń EP			Rdzeń PP		
	A	B	C	A	B	C
400 /2	315	250	200	-	-	-
400 /3	315	250	200	-	-	-
500 /3	400	315	250	-	-	-
500 /4	400	315	250	-	-	-
630 /3	500	400	315	400	315	250
630 /4	500	400	315	-	-	-
800 /3	630	500	400	400	315	250
800 /4	630	500	400	500	400	315
800 /5	630	500	400	-	-	-
1000 /3	630	500	400	500	400	315
1000 /4	800	630	500	630	500	400
1000 /5	800	630	500	630	500	400
1250 /3	800	630	500	630	500	400
1250 /4	800	630	500	630	500	400
1250 /5	1000	800	630	800	630	500
1400 /4	1000	800	630	630	500	400
1600 /4	1000	800	630	800	630	500
1600 /5	1000	800	630	800	630	500
1800 /4	1000	800	630	1000	800	630
1800 /5	1250	1000	800	1000	800	630